

CRYSTAL EYE SERIES 50



Australia's first Extended Detection & Response (XDR) solution and the World's most powerful XDR platform

Our Series 50 XDR security appliance is the ideal solution to defend against cyber threats supporting multiple internet connections of up to 10Gb/s each.

Crystal Eye 50 delivers powerful, flexible protection for enterprise environments across multiple devices. Combined with our range of integrated services, our high performance rack mount devices are an easy to deploy, easy to manage, effective security solution.

Through Crystal Eye's powerful threat intelligence system, the platform processes over 19-million Indicators of Compromise (IoC) per day using real-time visibility & analytics to enable automated actionable intelligence.

Complete XDR Platform

A#

Integrated XDR capabilities



Automated Actionable Intelligence



Multi-layered security delivering defence in depth



Built-In Compliance Feature Set



Risk Assessment Reports



Vulnerability Scanning

Full Network Control



Network Security Monitoring



Advanced deep-packet inspection and decryption



Instant SOC & embedded SIEM solution



On-demand PCAP forensic analysis and logging



Gateway application whitelisting



Extended log processing, retention & policy management controls

Firewall throughput:	34Gbps	The maximum capacity between two ports of the same bandwidth with no packet loss.
IDPS throughput:	2.5Gbps	The maximum volume of data that can be processed by the Intrusion Detection & Prevention modules with no packet loss.
True Security Throughput (TST):	1.4Gbps	The lab tested peak load with all security features turned on and processing a typical enterprise network profile: 76% http(s) web browsing, 12% real-time applications (VoIP, Video conferencing) and 12% other traffic types.

SPECIFICATIONS

Processing System

Intel Generation 13 Core i7 13700, 16 Cores, 5.2GHz Z790 Chipset, Socket 1700

Memory Capacity

32GB DDR5

Networking capacity

- ·1x Intel Gb WAN port
- ·1x Intel 10Gb WAN port
- · Quad GbE Network
- \cdot Quad x Intel 10Gb WAN port
- ·1x Dual SFP 10GbE

4 x USB 2.0 (Type A)

2 x USB 3.2 (Type A)

2 x USB 3.2 (Type C)

Stateful Inspection Firewall Features

- · Multiple Security Zones
- · Location-aware and Device-aware Identity-based Access
- Control Policy
- · Security Policies IPS, Web Filtering, Application Filtering, Anti-virus, Anti-spam and QoS
- · Policy based Source and Destination NAT, Gateway
- Specific NAT Policy · MAC & IP-MAC Filtering
- Spoof Prevention

Gateway Anti-Virus & Anti-Spyware Features

- · SSL Mismatch Detection
- · Cloaked URL Detection
- · Virus, Worm, Trojan Detection and Removal
- · Spyware, Malware, Phishing Protection
- · Scans HTTP, HTTPS, FTP, SMTP/S, POP3, IMAP, IM, SMB, VPN Tunnels
- · Customised Individual User Scanning
- · Scan and deliver by file size
- · Block by file types

Web Filtering Features

- · More than 130 categories
- · Auto category updates
- · Exception list
- · IP or hostname based
- · Controls based on URL, Keyword and File type
- · Protocols supported: HTTP, HTTPS
- Block malware, Phishing, Pharming URLs
 Block java Applets, Cookies, Active X, Google Cache pages
- · Data leakage control by blocking HTTP and HTTPS upload
- · Banned phrase list, YouTube for Schools
- · Custom Denied Message per Web Category

- · IPSEC VPN for site to site communications
- · Authentication Active Directory, LDAP, RADIUS,
- · Multi-layered Client Authentication Certificate, Username/Password
- · Lightweight SSL VPN Tunnelling Client
- TCP based Application Access HTTP, HTTPS, RDP, TELNET, SSH Wireguard SSL VPN

- · Al rule matching to detect anomalies in network traffic
- · Automatic defence rules from over 19 million IOC's processed daily
- · Machine learning smart detection of network based SSH attacks

End Point Application Whitelisting (CEASR)

- · Easy Device application mapping
- · Ability to whitelist known good device Applications from the gateway
- · Protect against Zero-day attacks
- · Deal with encrypted malicious traffic with one click

Advanced Compliance Features

- · Azure AD threat analysis
- · Vulnerability Scanning · DLP Alerting and Blocking

Intrusion Prevention System Features

- · 5 managed rule sets, comprising of 58k+ rules updated daily from the latest threats
- · HTTP/TLS/DNS Logging
- Actions Alert, Drop, Reject, Pass
 Auto IPS Updates from Red Piranha threat intelligence sharing platform
- Protocol Anomaly Protection

- SCADA, Ilot and IoT Aware
 VoIP and SIP protocol reporting
 Easy tuning in dashboards to reduce false positives

Application Filtering Features

- · Layer 7 (Application) & Layer 8 (User) Control and Visibility
- Inbuilt Application Category Database

 Visibility and Controls for HTTPS based micro-apps like Facebook chat, YouTube video upload

SD WAN Features

- ·TCP & UDP Tunnelling
- · Authentication Active Directory, LDAP, RADIUS, Local
- Multi-layered Client Authentication Certificate, Username/Password, MFA
- · Lightweight SSL VPN Tunnelling Client
- TCP based Application Access HTTP, HTTPS, RDP, TELNET, SSH

Bandwidth Management Features

- · QoS Policies
- · Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- · Data Transfer Report for multiple Gateways

- · Automated Fallover/Failback
- Interface types: Alias, Multisport Bridge, LAG (port trunking). VLAN, WWAN, TAP
- · Multiple DHCP Servers support
- · Supports HTTP proxy, Parent proxy with FQDN
- Dynamic Routing: RIP v1&v2, OSPF, BGP
- · IPv6 Support: Dual Stack Architecture: Support for IPv4 and IPv6 Protocols
- · IPv6 Route: Static and Source

Administration & System Management Features

- · Web-based configuration wizard
- · Role-based Access control · Firmware Upgrades via Web UI
- · Web 2.0 compliant UI (HTTPS)

- · Internal Database
- · Microsoft Active directory connector
- · Internal active directory server

Storage System/Optional Extended Storage (max)

System: 1x500GB M.2 NVMe Extended: 16TB SSD

 $W \times D \times H$ 428mm(w) 593.2mm(d) 88.6mm(h) Weight

General Details

1x HDMI port, NVMe M.2 Main Storage GEN4 5TB/sec transfer, 6Gb/s SATA 3 extended storage subsystem

Voltage spike protection

802.3az (Energy Efficient Ethernet) support

Certifications: FCC, CE

Input Voltage 110 VAC/220-240 VAC









